ClickShare CX-50

Premium wireless conferencing for large meeting rooms and boardrooms



- Full BYOD support
- Remote collaboration with Button or Desktop App
- Works with your device, conferencing platform & a wide range of AV solutions
- Advanced network and AV integration
- Enhanced security, connected and cloud managed
- Full interactivity
- HDMI input cable

In the hybrid workplace you need to ensure that your teams are continually in close collaboration with one another. ClickShare CX-50 is a premium agnostic wireless room system designed to facilitate exactly this. Connecting you in less than seven seconds and allowing users to participate in completely wireless and productive hybrid conferences.

Find out what's new in the latest ClickShare update

Interact, discuss, collaborate with remote participants in superior AV quality driving multi-content sharing

Superior wireless conferencing

ClickShare CX-50 brings superior, seamless one-click wireless conferencing. With our agnostic wireless room system, you start a hybrid meeting from your laptop, using any conference tool. No cables, no mess. Everyone is heard, everyone is seen, no matter where they are.

Walk in, connect automatically to room devices like cameras, mics, speakers, sound bars for a supreme AV quality. Works with large selection of compatible solutions from global partners and brands. Make hybrid collaboration flow in large meeting rooms and conference rooms with only one click.

Choose how you want to collaborate

With ClickShare CX-50, you can "bring your own meeting" and decide how you and your guests collaborate. Plug & play with the ClickShare Button and choose for smart, intent-based meeting flows powered by the ClickShare App to to make your meetings intuitive and interactive.

BARCO



It offers a range of capabilities for more effective collaboration in your medium-tolarge meeting rooms including annotation so meeting participants can add comments to slides, blackboarding so details can be updated in real time and complete touch-screen control through ClickShare CX-50 touchback support feature. Use the ClickShare Button and the ClickShare App for an intuitive and consistent user experience.

Better hybrid meetings? Yes! With smart, intuitive meeting flows in the ClickShare App

Smart intent-based meeting flows make your meeting experience stress-free.Walk into the room, you immediately see if the room is available or booked. Automatically connect to the meeting room (PresentSense ultrasound proximity detection) or plug in a Button. ClickShare guides you as a host or participant (HostFlow). Start the meeting from your personal calendar with a single click (One-Click-Join).

Share your presentation, keep track of remote participant's video, side by side (ConferenceView). Share full screen or application window, while keeping your laptop screen private for note taking. When you end the call, the meeting room becomes a digital signage display.

A user-friendly experience and enhanced security

A set of IT friendly features makes ClickShare Conference a perfect fit to any enterprise environment. ClickShare Conference, excelling in enhanced security, offers an advances network integration in any IT- network. With the XMS Cloud Management Platform you enjoy easy management of units, intuitive user experiences and clear analytics to drive your digital workplace.

For practical questions on the advanced network and AV integration options of the ClickShare Conference CX-50, check our technical support or get in touch with your Barco contact.

PRODUCT SPECIFICATIONS	CLICKSHARE CX-50
ClickShare Base Unit dimensions	
Dimensions (HxWxD)	39mm x 200mm x 202mm
Power supply	Standard 110/220 V AC plug
Power consumption	Operational: 50W (max) Standby:
Weight	900 gr
General specifications	
Operating system	Windows 10 or higher macOS 11 (BigSur) and higher. Android v11 and higher (ClickShare App) iOS 14 and higher (ClickShare App)
System requirements	For a smooth experience with Microsoft Teams or Zoom.
	Minimum: Intel i3 dual-core processor / 8GB RAM / OS : Windows 10 latest build or Mojave latest build
	Recommended: Intel i5 4-core processor / 8GB RAM / OS: Windows 10 latest build or Mac OS latest build
Video outputs	4K UHD (3840*2160) @ 30Hz. HDMI 1.4b
Video inputs	1920x1080 @30Hz. HDMI 1.4b
Audio output	USB, SPDIF, jack, HDMI
USB	3 X USB-A, 1 X USB-C
ClickShare Buttons	2
ClickShare App	Desktop & Mobile
Native protocols	Airplay, Google Cast, Miracast
	Maximum number of simultaneous connections (with Buttons and/or App): minimum 32
Maximum number of simultaneous connections (with Buttons and/or App)	32
Noise Level	Max. 25dBA @ 0-30°C Max. 30dBA @ 30-40°C
Authentication protocol	WPA2-PSK in stand alone mode WPA2-PSK or IEEE 802.1X using the ClickShare Button in network integration mode
Wireless transmission protocol	IEEE 802.11 a/g/n/ac and IEEE 802.15.1
Reach	Max. 30m (100 ft) between ClickShare Button and ClickShare Base Unit
	Frequency band 2.4 GHZ and 5 GHz (DFS)
Frequency band	
Frequency band Connections	Frequency band 2.4 GHZ and 5 GHz (DFS)
	Frequency band 2.4 GHZ and 5 GHz (DFS) 2.4 GHZ and 5 GHz (DFS channels supported in select number of countries) 1x Ethernet LAN 1Gbit 1x USB Type-C 2.0 (back); 2x USB Type A 2.0 (back); 1x USB Type A 2.0 (front)
Connections	Frequency band 2.4 GHZ and 5 GHz (DFS) 2.4 GHZ and 5 GHz (DFS channels supported in select number of countries) 1x Ethernet LAN 1Gbit 1x USB Type-C 2.0 (back); 2x USB Type A 2.0 (back); 1x USB Type A 2.0 (front) Audio analog line out on mini jack socket (3.5mm), digital S/PDIF Operating: 0°C to +40°C (+32°F to +104°F) Max: 35°C (95°F) at 3000m
Connections Temperature range	Frequency band 2.4 GHZ and 5 GHz (DFS) 2.4 GHZ and 5 GHz (DFS channels supported in select number of countries) 1x Ethernet LAN 1Gbit 1x USB Type-C 2.0 (back); 2x USB Type A 2.0 (back); 1x USB Type A 2.0 (front) Audio analog line out on mini jack socket (3.5mm), digital S/PDIF Operating: 0°C to +40°C (+32°F to +104°F) Max: 35°C (95°F) at 3000m Storage: -20°C to +60°C (-4°F to +140°F) Storage: 0 to 90% relative humidity, non-condensing
Connections Temperature range Humidity	Frequency band 2.4 GHZ and 5 GHz (DFS) 2.4 GHZ and 5 GHz (DFS channels supported in select number of countries) 1x Ethernet LAN 1Gbit 1x USB Type-C 2.0 (back); 2x USB Type A 2.0 (back); 1x USB Type A 2.0 (front) Audio analog line out on mini jack socket (3.5mm), digital S/PDIF Operating: 0°C to +40°C (+32°F to +104°F) Max: 35°C (95°F) at 3000m Storage: -20°C to +60°C (-4°F to +140°F) Storage: 0 to 90% relative humidity, non-condensing Operation: 0 to 85% relative humidity, non-condensing
Connections Temperature range Humidity Anti-theft system	Frequency band 2.4 GHZ and 5 GHz (DFS) 2.4 GHZ and 5 GHz (DFS channels supported in select number of countries) 1x Ethernet LAN 1Gbit 1x USB Type-C 2.0 (back); 2x USB Type A 2.0 (back); 1x USB Type A 2.0 (front) Audio analog line out on mini jack socket (3.5mm), digital S/PDIF Operating: 0°C to +40°C (+32°F to +104°F) Max: 35°C (95°F) at 3000m Storage: -20°C to +60°C (-4°F to +140°F) Storage: 0 to 90% relative humidity, non-condensing Operation: 0 to 85% relative humidity, non-condensing Kensington lock
Connections Temperature range Humidity Anti-theft system Certifications	Frequency band 2.4 GHZ and 5 GHz (DFS) 2.4 GHZ and 5 GHz (DFS channels supported in select number of countries) 1x Ethernet LAN 1Gbit 1x USB Type-C 2.0 (back); 2x USB Type A 2.0 (back); 1x USB Type A 2.0 (front) Audio analog line out on mini jack socket (3.5mm), digital S/PDIF Operating: 0°C to +40°C (+32°F to +104°F) Max: 35°C (95°F) at 3000m Storage: -20°C to +60°C (-4°F to +140°F) Storage: 0 to 90% relative humidity, non-condensing Operation: 0 to 85% relative humidity, non-condensing Kensington lock FCC/CE
Connections Temperature range Humidity Anti-theft system Certifications Touch screen support & Interactivity	Frequency band 2.4 GHZ and 5 GHz (DFS) 2.4 GHZ and 5 GHz (DFS channels supported in select number of countries) 1x Ethernet LAN 1Gbit 1x USB Type-C 2.0 (back); 2x USB Type A 2.0 (back); 1x USB Type A 2.0 (front) Audio analog line out on mini jack socket (3.5mm), digital S/PDIF Operating: 0°C to +40°C (+32°F to +104°F) Max: 35°C (95°F) at 3000m Storage: -20°C to +60°C (-4°F to +140°F) Storage: 0 to 90% relative humidity, non-condensing Operation: 0 to 85% relative humidity, non-condensing Kensington lock FCC/CE Touch screen support : Yes Interactivity : Yes
Connections Temperature range Humidity Anti-theft system Certifications Touch screen support & Interactivity Wireless conferencing	Frequency band 2.4 GHZ and 5 GHz (DFS) 2.4 GHZ and 5 GHz (DFS channels supported in select number of countries) 1x Ethernet LAN 1Gbit 1x USB Type-C 2.0 (back); 2x USB Type A 2.0 (back); 1x USB Type A 2.0 (front) Audio analog line out on mini jack socket (3.5mm), digital S/PDIF Operating: 0°C to +40°C (+32°F to +104°F) Max: 35°C (95°F) at 3000m Storage: -20°C to +60°C (-4°F to +140°F) Storage: 0 to 90% relative humidity, non-condensing Operation: 0 to 85% relative humidity, non-condensing Kensington lock FCC/CE Touch screen support : Yes Interactivity : Yes via App or Button
Connections Temperature range Humidity Anti-theft system Certifications Touch screen support & Interactivity Wireless conferencing Local view	Frequency band 2.4 GHZ and 5 GHz (DFS) 2.4 GHZ and 5 GHz (DFS channels supported in select number of countries) 1x Ethernet LAN 1Gbit 1x USB Type-C 2.0 (back); 2x USB Type A 2.0 (back); 1x USB Type A 2.0 (front) Audio analog line out on mini jack socket (3.5mm), digital S/PDIF Operating: 0°C to +40°C (+32°F to +104°F) Max: 35°C (95°F) at 3000m Storage: -20°C to +60°C (-4°F to +140°F) Storage: 0 to 90% relative humidity, non-condensing Operation: 0 to 85% relative humidity, non-condensing FCC/CE Touch screen support : Yes Interactivity : Yes via App or Button High quality
Connections Temperature range Humidity Anti-theft system Certifications Touch screen support & Interactivity Wireless conferencing Local view Network connection	Frequency band 2.4 GHZ and 5 GHz (DFS) 2.4 GHZ and 5 GHz (DFS channels supported in select number of countries) 1x Ethernet LAN 1Gbit 1x USB Type-C 2.0 (back); 2x USB Type A 2.0 (back); 1x USB Type A 2.0 (front) Audio analog line out on mini jack socket (3.5mm), digital S/PDIF Operating: 0°C to +40°C (+32°F to +104°F) Max: 35°C (95°F) at 3000m Storage: -20°C to -60°C (-4°F to +140°F) Storage: 0 to 90% relative humidity, non-condensing Operation: 0 to 85% relative humidity, non-condensing FCC/CE Touch screen support : Yes Interactivity : Yes via App or Button High quality LAN & WiFi (dual)

Last updated: 29 Aug 2022

Technical specifications are subject to change without prior notice. Please check www.barco.com for the latest information.

BARCO