

CAM540

Conference Camera











SmartFrame

4K Ultra HD

USB 3.1

Plug & Play

Bring Superior 4K Quality to your Collaboration

The CAM540 brings AVer's new SmartFrame auto-framing technology to 4K HD video conferencing. With a wide field of view, the CAM540 is guaranteed to provide an incredible communication experience in your meeting room.

A must have for your modern meeting room!



AVer SmartFrame Gets Your Meeting Started Fast

The CAM540 delivers AVer's latest camera technology to your meeting room with **AVer SmartFrame**. SmartFrame effortlessly puts everyone into frame instantly so you can start your meeting in seconds.



The CAM540 uses a high-end Sony 4K CMOS that provides users with an incredibly clear 4K video conferencing experience and with an 86° FOV and 16X zoom users can obtain the maximum amount of collaboration.



The CAM540 offers a new sleek and fluid design for your conferencing room. With USB3.1 Gen1 Type-C plug-and-play functionality and space saving design, the CAM540 easily fits your modern meeting room and provides an experience that both novices and experts can enjoy.







PRODUCT SPECIFICATIONS

Package Contents

- · Camera
- · Remote control
- · Power adapter
- · USB3.1 type-C to type-A Cable (6ft)
- · Quick-start guide
- Metal mount, tripod screw
- · Battery

Motorized Pan and Tilt Movement

- · Pan: ±160°
- · Tilt: +90° (up) -30° (down)
- · 10 camera presets (through remote control)
- \cdot Fast and quiet pan & tilt movement

Dimension

- · Package dimensions: 227*189*261mm
- · Package weight: 2.54 kg
- · Camera: 97.8 x 130.7 x 171.1 mm/1.5kg
- · Remote control: 200 x 50 x 21 mm/0.09kg

Camera

- · Ultra-crystal clear image support up to 4K
- · Frame rate: 4K, 1080p , 720p , 640x480, 320x240
- · SmartFrame: Automatic FOV adjustment to fit all participants
- · 16X Zoom
- · Auto focus: minimum working distance 1 meter
- \cdot 86° Wide field of view
- \cdot Back light compensation and 2D noise reduction technology for optimizing light balance in different conditions
- · Standard tripod screw holes
- · Analytics API: Enterprises and third-party software providers can obtain people-counting data for better understanding of meeting-space usage

Power Supply

- \cdot AC 100V ~240V, 50/60Hz, 3 meters
- · Consumption: 12V, 2A

Compatible Applications

Zoom, Microsoft® Teams, Skype for Business, Skype, Google Hangouts, Intel® Unite™, RingCentral, BlueJeans, V-Cube, LiveOn, CyberLink U Meeting®, TrueConf, Adobe Connect, Cisco WebEx®, Fuze, GoToMeeting™, Microsoft® Lync™, Vidyo, vMix, WebRTC, Wirecast, XSplit

FRONT



BACK



BACK PANEL





©2019 AVer Information Inc. All rights reserved. All brands and logos are trademarks of their respective companies.

